



**Central  
Diesel**

The Engine, Pump & Power Co.

---

# Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



# GP30AD

## Features

- Original Deutz oil cooled engine
- Original Mecc Alte Alternator
- Remote start controller
- Industrial muffler
- AVR\_s powered from AUX winding
- High Alternator start capacity

## Controller Display

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

## Controller Shutdowns

- Low oil pressure
- High temperature
- Low fuel level alarm (shutdown after 5 mins)
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown



## SPECIFICATIONS

Standby kVA	30
Standby kW	24
Prime kVA	27
Prime kW	22
Standby Amps	42
Prime Amps	38
Voltage	415
RPM	1500
Engine Model	F4M2011
Cylinders	4 In line
Fuel Tank Size	215 ltrs
Fuel Tank Running Time at 75% Load	45 hrs
Weight	710 kg
Dimensions	1750x700x1100mm
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Eco - AVR - 4 pole - Class H - IP21 Fuel Consumption: 6 Engine Brand: Oil-cooled, 4 stroke diesel Service Intervals: 500 Hours Power Factor: 0.8

