



**Central  
Diesel**

The Engine, Pump & Power Co.

---

# Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



# GPI 15AD

## Features

- Remote start controller
- Industrial mufflers
- AVR\_s powered from AUX winding
- High Alternator start capacity

## Controller Display

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

## Controller Shutdowns

- Low oil pressure
- High water temperature
- Low fuel level alarm (shutdown after 5 mins)
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown



## SPECIFICATIONS

Standby kVA	115
Standby kW	92
Prime kVA	105
Prime kW	84
Standby Amps	160
Prime Amps	146
Voltage	415
RPM	1500
Engine Model	BF4M1013EC
Cylinders	4 In line
Fuel Tank Running Time at 75% Load	24 hrs
Weight	1170 kg
Dimensions	2100x900x1400mm
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Echo - AVR - 4 pole - Clash H - IP21 Fuel Consumption: 24 Engine Brand: Water-cooled, 4 stroke diesel Service Intervals: 500 Hours Power Factor: 0.8