



**Central  
Diesel**

The Engine, Pump & Power Co.

---

# Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



# GPI 15SD

## 115 kVA 415V Silenced Three Phase Diesel Generator

### Features

- Remote start controller
- Noise level from 70 db(A) at 7 meters
- Large fuel tanks (30 hours\*)
- Single point lift compact footprint
- Skid bases/ forklift pockets (extra)

### Controller Displays

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

### Controller Shutdowns

- Low oil pressure
- High water temperature
- Low fuel level alarm
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown



## SPECIFICATIONS

Standby kVA	115
Standby kW	92
Prime kVA	105
Prime kW	84
Standby Amps	160
Prime Amps	146
Voltage	415
RPM	1500
Engine Model	BF4M 1013
Cylinders	4 In line
Fuel Tank Size	500
Fuel Tank Running Time at 75% Load	30 hrs
Weight	1660 kg
Dimensions	2850x1000x1400mm
Noise Level @ 7m	70
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Eco - AVR - 4 pole - Class H - IP21 Fuel Consumption: 24 Engine Brand: Deutz Water-cooled, 4 stroke diesel Service Intervals: 500 Hours Power Factor: 0.8