



**Central  
Diesel**

The Engine, Pump & Power Co.

---

# Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



# GPI 65AD

## 165 kVA 415V Three phase diesel Generator

### Features

- Remote start controllers
- Industrial mufflers
- AVR\_s powered from AUX winding
- High Alternator start capacity

### Controller Display

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

### Controller Shutdowns

- Low oil pressure
- High water temperature / low water level
- Low fuel level alarm (shutdown after 5 mins)
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown



## SPECIFICATIONS

Standby kVA	165
Standby kW	132
Prime kVA	150
Prime kW	120
Standby Amps	230
Prime Amps	209
Voltage	415
RPM	1500
Engine Model	BF6M1013EC
Cylinders	6 In line
Fuel Tank Running Time at 75% Load	24 hrs
Weight	1640 kg
Dimensions	2850x1000x1400mm
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Eco - AVR - 4 pole - Class H - IP21 Fuel Consumption: 32 Engine Brand: Water-cooled, 4 stroke diesel Service Intervals: 500 Hours Power Factor: 0.8