



**Central
Diesel**

The Engine, Pump & Power Co.

Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



GP220AD

220 kVA 415V Three phase diesel Generator

Features

- Remote start controllers
- Industrial mufflers
- AVR_s powered from AUX winding
- High Alternator start capacity
- Wireless starting 150m to 5klm**

Controller Display

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

Controller Shutdowns

- Low oil pressure
- High water temperature / low water level
- Low fuel level alarm (shutdown after 5 mins)
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown



SPECIFICATIONS

Standby kVA	220
Standby kW	176
Prime kVA	200
Prime kW	160
Standby Amps	306
Prime Amps	278
Voltage	415
RPM	1500
Engine Model	BF6M1013FC
Cylinders	6 In line
Fuel Tank Running Time at 75% Load	24 hrs
Weight	2000 kg
Dimensions	3000x1100x1650mm
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Eco - AVR - 4 pole - Class H - IP21 Fuel Consumption: 45 Engine Brand: Water-cooled, 4 stroke diesel Service Intervals: 500 Hours Power Factor: 0.8