



**Central
Diesel**

The Engine, Pump & Power Co.

Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



GP220SD

Features

- Remote start controllers
- Noise level from 70 db(A) at 7 meters
- Large fuel tanks (1400ltrs/42 hours)
- Single point lift compact footprint
- Skid bases/ forklift pockets (extra)

Controller Display

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

Controller Shutdowns

- Low oil pressure
- High water temperature / low water level
- Low fuel level alarm (shutdown after 5 mins)
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown



SPECIFICATIONS

Standby kVA	220
Standby kW	176
Prime kVA	200
Prime kW	160
Standby Amps	306
Prime Amps	278
Voltage	415
RPM	1500
Engine Model	BF6M1013FC
Cylinders	6 In line
Fuel Tank Size	1400 ltrs
Fuel Tank Running Time at 75% Load	42 hrs
Weight	2150 kg
Dimensions	3300x1100x1500mm
Noise Level @ 7m	70
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Echo - AVR - 4 pole - Clash H - IP21 Fuel Consumption: 45 Engine Brand: Deutz Water-cooled, 4 stroke diesel Service Intervals: 500 Hour- sPower Factor: 0.8