



**Central
Diesel**

The Engine, Pump & Power Co.

Product Specification

Central Diesel provides these specifications as a courtesy and are a guide only. They have been sourced from the manufacturer and may change without notice. Central Diesel accepts no responsibility for any errors or omissions.



GP66AD

Features

- Original Deutz Water cooled engine
- Original Mecc Alte Alternator
- Remote start controller
- AVR_s powered from AUX winding
- Large fuel tanks (470ltrs/47 hrs)
- Industrial mufflers

Controller Display

- Voltage
- Current
- Frequency
- Battery voltage
- Hour meter
- Fuel level
- Common alarm output available

Controller Shutdowns

- Low oil pressure
- High water temperature
- Low fuel level alarm (shutdown after 5 mins)
- High/Low A/C voltage
- High/Low frequency
- High/Low DC battery voltage
- Belt break shutdown



SPECIFICATIONS

Standby kVA	66
Standby kW	53
Prime kVA	60
Prime kW	48
Standby Amps	92
Prime Amps	83
Voltage	415
RPM	1500
Engine Model	BF4M 2012
Cylinders	4 In line
Fuel Tank Size	470 ltrs
Fuel Tank Running Time at 75% Load	47 hrs
Weight	1030 kg
Dimensions	2100x900x1300mm
Other Specifications	Overload: 300% for 20 seconds Alt Brand: Mecc Alte Eco - AVR - 4 pole - Clash H - IP21 Fuel Consumption: 14 Engine Brand: Water-cooled, 4 stroke diesel Service Intervals: 500 Hours Power Factor: 0.8